

Ridgewood

Silvertop Ash Decking

Eucalyptus Sieberi

Technical Information

Density (kg/m ³ dry)	850	Sapwood Lyctid Susceptible	No
Specific Gravity	0.68	Machining	Good
Modulus of Rupture (MPa dry)	136	Resistance to Split in Nailing	Fair
Modulus of Elasticity (GPa dry)	17	Resistance to Split in Screwing	Fair
Radial Shrinkage %	5	Gluing	Good
Tangential Shrinkage %	10.6	Growing Region	VIC & NSW
Hardness (Janka) (kN)	9.5	Availability	Available
Finish	Good		
Stability	Good		

Description

Silvertop Ash is a lighter decking material than some other species, but it is durable and easily nailed, which makes it an attractive decking option.

It is a straight-grained timber that often features gum veins, ambrosia, growth rings and pencil steaks which add individuality to any decking project. The colour palette ranges from pale to medium browns with a hint of pink.

Silvertop is a native Australian timber which is sustainably harvested from forests stretching from the mid-north of New South Wales to Tasmania in the south.

Silvertop Ash provides good fire resistance, and is one of seven hardwood species that was found suitable for construction in bush-fire prone areas.

Sizes
Pencil Round Four Corners
90mm × 22mm
140mm × 32mm

BAL
Bush-fire Attack Level 12.5, 19 & 29
All AS 3959 Required Applications

