

Ridgewood

Tasmanian Blackwood Flooring

Acacia Melanoxylon

Technical Information

Density (kg/m ³ dry)	665	Stability	Excellent
Specific Gravity	0.66	Sapwood Lyctid Susceptible	Yes
Modulus of Rupture (MPa dry)	99	Machining	Excellent
Modulus of Elasticity (GPa dry)	13	Resistance to Split in Nailing	Good
Radial Shrinkage %	1.5	Resistance to Split in Screwing	Good
Tangential Shrinkage %	4	Gluing	Good
Hardness (Janka) (kN)	6	Growing Region	TAS
Finish	Good	Availability	Widely

Description

Blackwood flooring is setting the mark for designer interiors. The rich texture and tones of the timber grown in north-west Tasmania's temperate rainforests is attracting interest from architects and designers nationally and internationally.

Traditionally a favourite for fine furniture makers, Blackwood flooring is now appearing in homes and commercial installations where warmth and a welcoming feel are paramount.

Blackwood flooring is a high-end product that brings a unique richness and depth to domestic and commercial projects. Renowned for its stability, and machined and dried to the highest standards, Blackwood stands the test of time.

Board Widths

Up to 160mm (wider boards on request)

Covers

2mm Overlay - 65×12, 85×12, 108×12, 133×12

Secret Nailing, End-Matched

65×19, 85×9, 108×19, 133×19, 160×19

