

Ridgewood

## Karri Flooring

*Eucalyptus Diversicolor*

### Technical Information

Density (kg/m <sup>3</sup> dry)	900	Stability	Good
Specific Gravity	0.88	Sapwood Lyctid Susceptible	No
Modulus of Rupture (MPa dry)	132	Machining	Fair
Modulus of Elasticity (GPa dry)	19	Resistance to Split in Nailing	Fair
Radial Shrinkage %	4.5	Resistance to Split in Screwing	Fair
Tangential Shrinkage %	10	Gluing	Fair
Hardness (Janka) (kN)	9	Growing Region	WA
Finish	Good	Availability	Widely

### Description

Karri is a Western Australian member of the eucalyptus family known for its hardness and earthy, deep red to pink tones.

A versatile timber, its colour palette works well alongside iron, steel and gloss, as well as more traditional materials.

Karri flooring adds a touch of class to interiors and has become a popular choice among leading architects and designers.

A Janka (hardness) rating of 9 means it is extremely tough, making Karri flooring an ideal choice for commercial applications where good looks and durability are paramount.

#### Sizes

Tongue & Grooved Secret Nailed End Matched  
19×80

Tongue & Grooved Overlay

14×85

14×105

Ridgewood Timber can supply matching stair componentry and stair treads.

